

Roadcrew Range Traffic Film Remover

A high powered concentrated cleaner specially formulated for the cleaning and removal of traffic film, heavy greasing and stubborn ingrained soiling. It is suitable for all vehicles, engines, components and chassis.



Available as:

TFR Rhodium
25 Litres RCH0008

TFR Platinum
25 Litres RCH0009

TFR Platinum
205 Litres RCH0010

Rhodium TFR

RCH0008

Rhodium TFR RCH0008	
Application	Powerful Traffic Film Remover for Heavy Duty Applications
Features & Benefits	<ul style="list-style-type: none">• Super Concentrate – Excellent Economy in Use• High Foam Formulation – Enhanced Detergency• Low Caustic Formula – Better Rinsing, Better Safety
Dilution	Pre-diluted 4:1 to give a TFR that can be used as outlined below: Light Soiling: 1% (100:1) Medium Soiling: 2% (50:1) Heavy Soiling: 3% (30:1)
Equipment Required	<ul style="list-style-type: none">• Pressure washer• Suitable dilution vessel• Bucket/Mop• Water supply
Use Instructions	<ol style="list-style-type: none">1. Roadcrew Heavy Duty TFR should be diluted 4:1 prior to dosing into your pressure washer. Diluted product can be used hot or cold in the normal way via a pressure washer. For best results use hot.2. Apply the solution to the surface of the vehicle at low or high pressure working from the bottom of the vehicle upward to avoid cleaning-streaks over dry areas of the vehicle.3. In hot weather cool paintwork with water before applying chemical. Do not allow the chemical to dry on the surface.4. Rinse with a bucket, hose or pressure washer from the top of the vehicle rinsing downwards evenly and methodically.
Hints & Tips	For a perfect spot-free finish dry with a squeegee or chamois. For the very best results, use warm water (<60°C at machine). To avoid cleaning-streaks, always work from bottom to top of vehicle.
Precautions	Always observe precautions in material safety data sheet. For fresh or damaged paint/livery always check compatibility on an inconspicuous area first.

Platinum TFR

RCH00009 & RCH0010

Application	Traffic Film Remover - Value, Performance and Versatility
Features & Benefits	<ul style="list-style-type: none"> • NTA-Free – safer to use • Optimised performance at minimised cost • Biodegradable formulation • Versatile – manual or pressure washer use
Dilution	Light Soiling: 2% (50:1) Medium Soiling 3% (30:1) Heavy Soiling 5% (20:1)
Equipment Required	<ul style="list-style-type: none"> • Pressure washer • Suitable dilution vessel • Bucket/Mop • Water supply
Use Instructions	<ol style="list-style-type: none"> 1. Roadcrew Frequent Use TFR may be used hot or cold via a pressure washer. For best results use hot. 2. Suitable dilutions are normally established by experience. See guidance above. 3. Apply the solution to the surface of the vehicle at low or high pressure working from the bottom of the vehicle upward to avoid cleaning-streaks over dry areas of the vehicle. 4. In hot weather cool paintwork with water before applying chemical. Do not allow the chemical to dry on the surface. 5. Rinse with a bucket, hose or pressure washer from the top of the vehicle, rinsing downwards evenly and methodically.
Hints & Tips	For the very best results, use warm water (<60°C at machine) To avoid cleaning-streaks, always work from bottom to top of vehicle.
Precautions	Always observe precautions in material safety data sheet, For fresh or damaged paint/livery always check compatibility on an inconspicuous area first.

Issue No. 3

Issue Date: 13/04/2017

Terms and conditions apply. Please go to www.road-crew.com for further details.

Roadcrew is a trading division of Volvo Group UK Limited registered in the United Kingdom with company number 02190944 whose registered office address is at Wedgnoek Lane, Warwick, CV34 5YA.